

## PART 1 - GENERAL

### 1.1 REFERENCES

The publications listed below form a part of this specification to the extent referenced. The publications are referred to in the text by the basic designation only.

#### ARCHITECTURAL & TRANSPORTATION BARRIERS COMPLIANCE BOARD (ATBCB)

ATBCB ADA TITLE III	(1990) Americans with Disabilities Act - Buildings and Facilities
---------------------	--

### 1.2 SUBMITTALS

Submit the following in accordance with Section 01330, "Submittal Procedures."

#### 1.2.1 SD- 02, Manufacturer's Catalog Data

- a. Hardware
- b. Fittings
- c. Toilet partitions, panels
- d. Hook and bumper

Submit literature for each item and each type of panel, complete with descriptions of materials, finishes, fastening and anchoring devices, and appurtenances.

#### 1.2.2 SD- 04, Shop Drawings

- a. Toilet partitions

Submit shop drawings indicating elevations of partitions, full- scale sections, thicknesses and gauges of metal, fastenings, proposed method of anchoring, the size and spacing of anchors, details of construction, hardware, fittings, mountings, and other related items and installation details.

### 1.3 DELIVERY, STORAGE, AND HANDLING

Deliver materials to the site in original sealed containers or packages, bearing the manufacturer's name, brand designation, specification number, type, style, and finish as applicable. Store and handle materials in a manner to protect them from damage.

## PART 2 - PRODUCTS

### 2.1 TOILET PARTITIONS

#### 2.1.1 Toilet Enclosures

Floor supported metal panel enclosures. Reinforce panels to receive partition-mounted accessories. Reinforce panels to receive through-the-panel double access accessories.

- a. Refer to Section 10800, Toilet Accessories

#### 2.1.2 Urinal Screens

Wall hung metal panel screens. Secure wall hung urinal screens with a minimum of three wall stirrup brackets.

#### 2.1.3 Operating Hardware and Fittings

Stainless steel door latches that operate without either tight grasping or twisting at the wrist of the operator. Latching devices and hinges for handicap compartments shall comply with ATBCB ADA TITLE III.

#### 2.1.4 Hook and Bumper

Model No. 915 Bradex or equal– Hook and Bumper. Project 3” stainless steel.

### 2.2 FINISHES

Partitions, panels, screen, and door finishes shall be stainless steel.

## PART 3 - EXECUTION

### 3.1 INSTALLATION

Secure the work to contiguous construction straight and plumb, with uniform clearance of 1/2 inch between pilasters and panels; one inch between pilasters and walls, and panels and walls; and not more than 3/16 inch between pilasters and doors. In the finished work, conceal evidence of drilling in floors and walls. Screws and bolts shall be stainless steel.

### 3.2 ADJUSTING

Adjust hardware for proper operation and set hinges to hold the doors ajar about 30 degrees when unlatched.

### 3.3 CLEANING

After installation, thoroughly clean exposed surfaces and restore damaged work to its original condition or replace with new work.

END OF SECTION